A SIGNAL TRANSFER POINT WITH INTERNET PROTOCOL CAPABILITY WITHIN A TELECOMMUNICATIONS NETWORK

BACKGROUND OF THE INVENTION

Technical Field of the Invention

[0001]   The present invention relates to telecommunications networks and, in particular, to routing Signaling System 7 (SS7) over an Internet Protocol (IP) based communications network.

Description of Related Art

[0002]   A typical telecommunications switch or exchange is a complex digital

processor comprising a vast number of devices, signal terminals and, most importantly,

software and hardware modules for providing telecommunications services to

telecommunications users. With the development of the aforementioned digital processor

and a Common Channel Signaling (CCS) network system, such as a Signaling System 7

(SS7) telecommunications network, a typical telecommunications network is now able to

support and transport much more than mere voice data. Such data might include video

images, control signals, or application specific information.

[0003]   Also with the wide proliferation of Internet Protocol (IP) based

communications networks, otherwise also known as the Internet, a number of

telecommunications vendors and service providers are interworking or interfacing the

existing CCS network system with the newly developed IP based communications

networks. Such an interface would enable an end user, such as a telecommunications

subscriber, to communicate multimedia data over a packet based communications network

rather than over a conventional CCS network system. Such an interface provides a number

of advantages such as higher bandwidth connections. As an illustration, a first Public

Switched Telephone Network (PSTN) subscriber connected to a first local switch communicates with a second PSTN subscriber connected to a second local switch over an IP network using a higher bandwidth connection than conventionally available over an SS7 telecommunications network. Such an interconnection is further advantageous since it is more economical to provide an IP connection than to establish or maintain an SS7 telecommunications network.

[0004]   Now referring to Fig. 1, a block diagram of a local switch connected to an Internet Protocol (IP) based communications network using an interworking function (IWF) is illustrated. A local switch 10A serving a plurality of subscriber terminals (not shown in Fig. 1) determines whether a destination node, such as a destination local switch 10B, is communicable over an IP network 110. In response to such a determination, the local switch communicates with an interworking function (IWF) 35A via an interface (IT) 37A to convert the SS7 signal to acceptable IP format and transmits the data over the IP network 110 to another IWF 35B connected to the destination local switch 10B. The actual mechanism and the specifications for converting or encapsulating the SS7 signal within an IP packet will not be disclosed in detail herein. A standardization organization called Internet Engineering Task Force (IETF) has formed working group Signal Transport

(SIGTRAN) within its Transport Area to formulate and implement the necessary specifications for transporting SS7 signal over an IP transport network. All such standardization specifications as mandated by IETF SIGTRAN working group are fully incorporated by reference herein.

[0005]   On the other hand, in response to a determination that the destination node is not connected to an IP network, the local switch 10A transmits necessary SS7 signals over to the connected SS7 network over its trunk interface 38A. In a conventional manner, the SS7 telecommunications network then communicates the call setup signal over to the destination local switch 10C for effectuating voice/data communication therebetween.

[0006]   However, as described above, a digital local switch is a complex and sophisticated processor and it is not desirable to modify or alter an existing local switch to interface or interconnect to the new IP network. Furthermore, such a change at the switch level requires each and every local switch within a particular telecommunications network to be modified to interface to the IP IWF 35A. Lastly, it fails to utilize the reliability and robustness that is already provided within the existing SS7 telecommunications network. Accordingly, there is a need for a network solution wherein local switches transparently

connect and interface with IP networks without requiring undesirable or complex changes therein.

SUMMARY OF THE INVENTION

[0007]   The present invention provides a method and apparatus for interfacing or connecting local switches within SS7 telecommunications networks with packet based Internet Protocol (IP) communication networks utilizing Signal Transfer Points (STPs) as interworking function (IWF).

[0008]   In one embodiment, the present invention provides a system and method for receiving local switch transmitted SS7 signals by a serving Signal Transfer Point (STP) and determining whether the destination node specified by the received SS7 signal is addressable over a connected IP network.

[0009]   In another embodiment, the present invention provides a system and method for determining the IP address for an application service provider (ASP) associated with a destination STP serving a specified destination local switch;

[0010]   In another aspect, the present invention provides a system and method for

encapsulating SS7 signals into IP packets and transporting the IP packets over an IP

network by a Signal Transfer Point (STP) serving a particular local switch within an SS7

telecommunications network.

[0011]   In still another aspect, the present invention provides a system and method

for maintaining two separate routing tables for routing SS7 signals over an IP network as

well as SS7 telecommunications network.

[0012]   In yet another aspect, the present invention provides a system and method

for updating a plurality of STPs and associated IP routing tables by a centralized server

connected to said plurality of STPs via an IP network.

BRIEF DESCRIPTION OF THE DRAWINGS

[0013]   A more complete understanding of the method and apparatus of the present

invention may be had by reference to the following detailed description when taken in

conjunction with the accompanying drawings wherein:

[0014]   FIGURE 1 is a block diagram of a local switch connected to an Internet

Protocol (IP) based communications network using an interworking function (IWF);

[0015]   FIGURE 2 is a block diagram of a Signaling System 7 (SS7) based

telecommunications network;

[0016]   FIGURE 3 is a block diagram illustrating the connection of a local switch

to an IP based communications network using a signal transfer point (STP) in accordance

with the teachings of the present invention;

[0017]   FIGURE 4 is a block diagram of a signal transfer point (STP) connected to

an IP based communications network in accordance with the teachings of the present

invention;

[0018]   FIGURE 5 is a block diagram illustrating the data structure of a routing

table associated with a serving STP in accordance with the teachings of the present

invention;

[0019]   FIGURE 6 is a block diagram illustrating the use of IP protocol to communicate SS7 signals in accordance with the teachings of the present invention;

[0020]   FIGURE 7 is a block diagram illustrating the protocol stack for implementing the SS7-to-IP conversion in accordance with the teachings of the present invention.

[0021]   FIGURE 8 is a flowchart illustrating the steps performed by an STP to communicate SS7 signal over an IP based communications network in accordance with the teachings of the present invention; and

[0022]   FIGURE 9 is a block diagram illustrating a centralized server connected to a plurality of STPs for updating associated routing code address table in accordance with the teachings of the present invention.

DETAILED DESCRIPTION OF THE DRAWINGS

[0023]   Figure 2 is a block diagram of a typical SS7 telecommunications network. As illustrated, the CCS-SS7 network is fully connected for reliability and robustness. The

PATENT APPLICATION PAGE 8

United States, for example, is divided into ten (10) regions and each of the ten regions has

at least two interconnected and duplicated Signal Transfer Points (STPs) 20A and 20B. As

illustrated, the regional STP 20A is augmented by the area STP 20B for reliability. The A-

link 30 provides access to the SS7 network from a local switch 10 where the local switch

10A is also connected to both STPs 20A and 20B for reliability. The STPs, such as 20A

and 20C located within different regions in the network are themselves interconnected by

so called B-links 50, while duplicate STPs in a region are connected by C-links 40. The

hierarchy of the CCS-SS7 architecture allows the addition of a new node or switch to the

network with minor adjustments. Because each region is also supported by two STPs and

two A-links and B-links as illustrated, it provides great reliability and robustness. If a

particular STP or an associated link goes down or becomes unavailable, the network

reroutes the data and maintains its network reliability automatically. Also, because of its

addressing mechanism and global title translation provided within its routing table (RT)

210A-D, a local switch transmits data without needing to know exactly where the

destination switch is located.

[0024]   FIGURE 3 is a block diagram illustrating the connection of a local switch

10A to an IP based communications network 110 using a signal transfer point (STP) 20A

in accordance with the teachings of the present invention. In order to fully utilize the signal

address translation mechanism within an existing SS7 telecommunications network and to

avoid the need for making changes within local switches, the local switch 10A interfaces

with an associated STP 20A in a conventional manner. As fully described above, each

local switch 10A is connected to a pair of STPs for reliability, but only one STP is

illustrated herein for simplicity.

[0025]   The STP 20A is, in turn, connected to the serving SS7 telecommunications

network using a pair of B-links 50 in a conventional manner as well. However, in

accordance with the teachings of the present invention, the serving STP 20A is further

connected to the IP network 110 using an IP connection 60, such as an Ethernet connection

link as illustrated. When an SS7 signal is received from the original local switch 10A over

a trunk interface 30, the original STP 20A first determines whether the destination address

specified by the received SS7 signal is addressable or reachable over the connected IP

network 110. In response to a determination that the specified destination node is also

connected to the IP network, the original STP 20A transforms the received SS7 signal to

be transportable over the IP network 110 and transmits the newly created IP packets to an

STP 20C serving the destination local switch 10B. Upon receiving the IP packets

transmitted by the originating STP 20A, the destination STP 20C decapsulates the received

SS7 data and forwards the received SS7 signals over to the specified destination local

switch 10B.

[0026]   Accordingly, all of the functions and determinations performed by the

originating and destination STPs have been performed transparently to the two local

switches and the two local switches communicate SS7 signal in a conventional manner

without knowing or realizing that the signals have been alternatively transmitted over a

different IP network.

[0027]   On the other hand, in response to a determination that the specified

destination address is not communicable over the IP network 110, the serving STP 20A

communicates the received SS7 signal over a link 50 to the connected SS7 network 100 in

a conventional manner.

[0028]   Now referring to Figure 4, a block diagram of a signal transfer point (STP)

connected to an IP based communications network in accordance with the teachings of the

present invention is illustrated. A first trunk interface module (IT) 120 within the serving

STP 20A provides an interface to the local switch 10A via a trunk interface link 30. As SS7 signals are transmitted by the local switch (also known as end-office and exchange), a processor 200 associated with the first interface module 120 determines whether a destination node specified within the received SS7 signal is addressable over a connected IP network. In accordance with the teachings of the present invention, the processor first reviews the SS7 routing table (RT) 210 to determine the routing context associated with the routing code specified by the received SS7 signal as the destination address. As an example, the "upward" routing context indicates that the specified routing code can be identified within a separate IP routing table 220 and thereby indicating that the signal can be communicated over an IP network. On the other hand, the "downward" routing context indicates that the specified routing code needs to be communicated cover an existing SS7 network by referencing the appropriate SS7 point code (PC).

[0029]   In response to a determination that the specified routing context is upward, the processor 200 then reviews the IP routing table (220) stored within the serving STP 20A. The IP routing table (220) then determines the routing code for the application service provider (ASP) associated with a STP serving the specified destination node and then determines the IP address associated thereto. An interworking function (IWF) module

PATENT APPLICATION PAGE 12

connected to the processor 200 then receives the transmitted SS7 signal and encapsulates

the SS7 application layer data within an IP packet using the determined IP address as the

destination address. An IP interface (IT) module 130 within the serving STP 20A then

transmits the encapsulated SS7 signals over an IP link 60 to the determined ASP in

accordance with the teachings of the present invention.

[0030]   However, in response to a determination that the routing context is

downward instead, the processor determines the proper routing code within the SS7 routing

table 210 and transmits the SS7 signal over an SS7 link 50 via an SS7 interface (IT) 140

in a conventional manner.

[0031]   FIGURE 5 is a block diagram illustrating the data structure of a routing

table 800 associated with a serving STP in accordance with the teachings of the present

invention. As more fully described in Fig. 4, the processor 200 (not shown in Fig. 5) takes

a particular point code associated with a destination node and determines whether the

identified destination node is communicable over an associated IP network. In accordance

with the teachings of the present invention, a particular point code value 800 is referenced

with a routing context. An exemplary implementation of such a reference is disclosed in

Fig. 5 wherein a binary value of one (1) 820 indicates that the routing context is "upward"

and that the specified routing code 810 can be identified within a separate IP routing table

220. On the other hand, the next routing code 810 is associated with a binary value of zero

(0) indicating a downward routing context and that the destination node needs to be

communicated over an existing SS7 network. It is to be understood that this routing table

800 may be incorporated within the same SS7 routing table 210 (not shown in Fig. 5) or

maintained as a separate routing table within a serving STP.

[0032]   FIGURE 6 is a block diagram illustrating the use of IP protocol to

communicate SS7 signals in accordance with the teachings of the present invention. As

shown in Fig. 6, the SS7 protocol basically has two parts: a user part comprising levels 4-7

and a message part comprising levels 1-3. The user part comes in several varieties, each

one corresponding to higher-layer protocols that enable user functions, possibly on

dissimilar machines, to communicate with one another. Examples of such user parts

include a Telephone User Part (TUP) 570 for basic telephone service, and an Integrated

Service Digital Network (ISDN) user Part (ISUP) 560 for providing combined voice, data

and video services. These user parts make use of the network delivery services provided

by the Message Transfer Part (MTP) 500, which provides a connectionless (diagram-type)

but sequenced transport service. The MTP layer 500 is further divided into three levels. The lowest level, MTP level one 508, is equivalent to the OSI physical layer and defines the physical, electrical and functional characteristics of the digital link. Next, MTP level two 507 ensures accurate end-to-end transmission of a message across a signaling link. In essence, the MTP level two 507 implements flow control, message sequence validation and error checking so that when an error occurs on a signaling link, the message (or set of messages) is retransmitted. The final layer of MTP 500, MTP level three 505, provides message routing between signaling points in the SS7 Network. MTP level three 505 reroutes traffic away from failed links and controls traffic when congestion occurs.

[0033]   The function block labeled Signal Connection Control Point (SCCP) 510 then provides the conversion from the MTP 500 to the network service specified by the Open System Interconnection (OSI) model.

[0034]   It is apparent from Fig. 6 that different user parts interface with the message transfer part (MTP) 500 at different points in the hierarchy. For example, application data level using Transaction Capability Application Part (TCAP) 540 need to interface with the TCAP level 530, the Intermediate Services Part (ISP) 520, and the SCCP 510 to interface

with the MTP 500. On the other hand, the ISUP 560 and the TUP 570 interface with the

MTP 500 directly. In accordance with the teachings of the present invention, the STP

serving a particular local switch uses a routing table 550 interfacing between the MTP 500

and the different user parts and determines that the destination node is reachable over an

associated IP network and replaces the MTP 500 portion of the received SS7 signal with

the IP transport part. Accordingly, the MTP3 User Adaptation Layer (M3UA) 580, Stream

Control Transmission Protocol (SCTP) 590 and Internet Protocol (IP) 600 replace the

transport part 500 of the SS7 signal to be transported over the IP network connected to the

serving STP. The serving STP performs such a transformation by encapsulating the

received SS7 signal within an IP packet using the determined IP address associated with

the serving ASP assigned to the destination STP as fully described above.

[0035]   In Figure 7, a block diagram illustrating the protocol stack for implementing

the SS7-to-IP conversion is shown in accordance with the teachings of the present

invention. Essentially the conversion means comprises a set of conversion layers or

protocol layers within the STPs 20A, 20B that permit direct peer-to-peer communications

between the STPs 20A, 20B. Essentially, the protocol layers provide the SS7 interface and

the IP interface within the STPs.

[0036]   As shown, SS7 signaling traffic is transmitted by a first local exchange 10A

to a first STP 20A. Within the local exchange 10A, the TCAP layer 530, SCCP layer 510,

MTP3 layer 505, a MTP2 layer 507, and a MTP1 layer 508 are applied to the traffic

according to well known protocol standards. The signaling traffic then proceeds through

an SS7 link 30 and into STP 10A. STP 10A receives the SS7 signaling traffic and applies

MTP1 layer 508, MTP2 layer 507, a MTP3 layer 505, optionally uses SCCP layer 510,

Nodal Interworking Function (NIF) layer 565, MTP3-User Adaptation Layer (M3UA) 580

and Stream Control Transmission Protocol (SCTP) 590 as appropriate. Alternatively, the

local exchange or other signaling end point may utilize ISUP or TUP. NIF Layer 565

within STP 20A serves as the interface between the MTP3 layer 505 and M3UA layer 580.

NIF layer 565 has no visible peer protocol within STP 20 but provides network status

information to one or both sides of the network.

[0037]   SCTP 590 is familiar to those skilled in the art. SCTP is a specialized

transportation protocol that has been developed for communications applications. SCTP

590 is designed to take the place of TCP, which is commonly used in Internet transactions

across an IP network. M3UA 580 is a protocol that supports the transport of any SS7

MTP3-User signaling (e.g., SCCP messages) over an IP network using the services of the

SCTP layer 590. Additionally, M3UA layer 580 contains protocol elements enabling a

seamless operation of the MTP3-User peers in the SS7 and IP domains. M3UA layer 580

is designed to be used between a signaling gateway and a Media Gateway Controller

(MGC) or IP-resident Database. The invention takes advantage of this feature of M3UA

to permit IP-enabled end nodes that conform to M3UA/SCTP protocol to inter-operate

within the IP network and to support communications over the IP link 60. Thus, the fact

that STPs 20A, 20B include M3UA layer 580 ad SCTP layer 590 provides a mechanism

for peer-to-peer communications over IP link 60.

[0038]   Reference is now made to FIGURE 8 illustrating a flowchart with the steps

performed by a STP to communicate SS7 signal over an IP based communications network

in accordance with the teachings of the present invention. A serving STP connected to a

particular local switch within an SS7 telecommunications network receives a SS7 signal,

such as an outgoing call connection request at step 300. The serving STP then reviews the

associated SS7 routing table to determine whether the specified destination address is

reachable by an IP network at step 310. In response to an affirmative determination

(decision link 350) that the IP network is available for the destination node at step 320, the

serving STP determines the routing code for the Application Service Provider (ASP)

associated with a STP serving the specified destination local switch at step 360. Using the

IP routing table, the serving STP then determines the IP address associated with the

identified ASP. Using the determined IP address for the ASP as the destination address,

the STP then encapsulates the received SS7 signal within an IP packet at step 370. The

newly created IP packet is then transmitted over the connected IP network at step 380. At

the reception end, the destination STP identified by the determined ASP routing code then

receives the transmitted IP packet at step 390 and removes the encapsulated SS7 signal data

therein at step 400. By reviewing the original destination address stored within the

decapsulated SS7 signal, the destination STP thereafter determines the destination local

switch at step 410. The destination STP then transmits the SS7 signal over to the identified

destination node over an SS7 link at step 420 in accordance with the teachings of the

present invention.

[0039]   On the other hand, in response to a negative determination (decision link

330) that the IP network is not available for the destination node, the serving STP then

determines whether an SS7 link is nevertheless available for the specified destination node

at step 340. If the destination routing code is specified within the routing table (decision

link 344), the serving STP transmits the received SS7 signal over a connected SS7 network

at step 345. Lastly, in response to a determination that the specified address is not specified within the routing table stored within the serving STP (decision link 346), the serving SS7 returns a SS7 address error to the originating local switch at step 348.

[0040]   As an illustration, such SS7 signals communicated by a serving STP includes application layer SS7 packet signals, such as TCAP based protocols that access application services. Such application services include Mobile Application Protocol (MAP) based services or signals, Intelligent Network (IN) invocation of services in an Service Control Point (SCP), or performing a global title (GT) translation service.

[0041]   Accordingly, in accordance with the teachings of the present invention, other than the STPs intercepting the SS7 signals and rerouting them over an IP network, the local switches are transparent to the IP communication and no changes or modifications are required at the local switch level.

[0042]   FIGURE 9 is a block diagram illustrating a centralized server 710 connected to a plurality of STPs for updating associated routing code address tables in accordance with the teachings of the present invention. In order for the serving STPs to properly

communicate SS7 signals over an IP network and as new nodes are being connected to the

IP network, the IP routing table 220 within each STP 20A-20D needs to be updated on a

regular basis. Since IP address data as well as routing code data need to be provided and

updated within each routing table, a different mechanism than a conventional IP address

updating scheme needs to be utilized. In accordance with the teachings of the present

invention, a centralized server 710 broadcasts the updated table on a regular basis to all of

the STPs connected to the IP network 110. The IP routing table 220 within each STP 20A-

20D connected to the IP network 110 is then replaced with the data received from the

update message transmitted by the centralized server 710 over an IP link 700A-D. As fully

described above, the interworking function (IWF) 230 residing within the serving STP then

utilizes the updated IP address to encapsulate and transmit SS7 signal over an IP network.

[0043]   Although a preferred embodiment of the method and apparatus of the

present invention has been illustrated in the accompanying Drawings and described in the

foregoing Detailed Description, it will be understood that the invention is not limited to the

embodiment disclosed, but is capable of numerous rearrangements, modifications and

substitutions without departing from the spirit of the invention as set forth and defined by

the following claims.